

Crane Scale Dynafor™ LLZ2



Product information



Wireless digital dynamometer

Specifications :

- Capacity range from 1t up to 250t
- Radio-Frequency 2.4GHz chipset for wireless range up to 400m with Tractel® Dynafor HHD, large displays AL128 & AL63, DMU and software accessories
- Bluetooth chipset for a connection to any smartdevice equipped with our free app', up to 30m
- Both Bluetooth and Radio-Frequency 2.4 GHz available
- 0.2% accuracy of full scale
- Powered by 3 AA batteries
- IP 65

Temperature range: -20°C up to +50°C.

Safety factor: 4:1.

Part Code	WLL ton	Model	Test load tons	Increment kg	Resolution 0.3% FS ± kg	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg
423500100050	1	LLZ2 1t	1.5	1	3	191	164	22	83,5	22	19,8	36,4	37,6	0.75
423500320050	3.2	LLZ2 3.2t	4.8	5	9.6	191	164	22	99.5	22	19,8	36,4	44,8	0.93
423500630050	6.3	LLZ2 6.3t	9.6	10	18.9	236	184	28	121.5	22	19,8	36,4	54,7	1.44
423501250050	12.5	LLZ2 12.5t	18.75	20	37.5	277	226	42	120.5	45	40,5	59,4	60,0	3.22
423502000050	20	LLZ2 20t	30	50	60	342	264	54	147	45	40,5	59,4	73,5	4.95

Blueprint

