

Anchorage Point PSA-YEP



Product information



- Rotates through 360° adjustable in the direction of the load.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Passed 150 kg dynamic fall testing (EU standard is 100 kg).
- Meets all requirements of the German BG BAU (Employer.s insurance association of the building industry).
- Correspond to the European Directive for "personnel protection equipment" (89/686/EWG).
- PSA - Lifting point to be as an anchor point for personal protective equipment.

Features: Built-in RFID/NFC chip

Material: Manufactured from forged alloy steel, quenched and tempered

Marking: According to standard, number of persons, standards, individual serial number, manufacturer, production year, product ID

Finish: Yellow Painted

Standard: EN 795, EN 365, EN 50308

Part Code	Max. number of persons	Torque Nm	thread M	Thread length (E) mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	S mm	W mm	Weight kg
84158281007	1	10	M12 x 1.75	19	45	30	10	11	18	33	29	5	45	8	52	0.2
84158281015	2	30	M16 x 2	24	52	35	14	13	24	35	33	8	52	10	61	0.3
84158281023	2	70	M20 x 2.5	30	60	40	16	15	30	44	37	7	60	12	70	0.6

Blueprint

