


Offshore crane



Piling crane



Mobile port crane



Steel Wire Rope Verotop P

Product information



Wire rope construction: Verotop P is a rotation-resistant rope with compacted strands and a rope core covered with a plastic layer.

Features:

- Very high breaking strength.
- Provides a very stable rope structure and achieves excellent bending fatigue results.
- Offers excellent crushing and very good abrasion resistance.
- Possesses perfect spooling behavior on multilayer drum.

ISO 4309 Rope Category No: All Diameters **RCN.23-3.**

Marking: According to standard

Standard: EN 12385-4

Note: verotop P can be used either with or without swivel.

Fill factor: 0.73

RCN: 23-3

Tolerance Ø: +2% to +4%

Part Code	Rope Diameter, mm	Steel area mm ²	Min. Breaking force		Weight kg/100m
			kN. 1960 N/mm ²	kN. 2160 N/mm ²	
104101606270149	16	147	241.7	252.7	125
104101706270149	17	166	272.8	285.3	141
104101806270149	18	186	305.8	319.8	158

104101906270149	19	207	340.8	356.3	176
104102006270149	20	229	377.6	394.8	195
104102106270149	21	253	416.3	435.3	215
104102206270149	22	277	456.9	477.7	236
104102246270149	22.4	283	473.6	495.3	240
104102306270149	23	303	499.3	522.2	258
104102406270149	24	330	543.7	568.6	281
104102506270149	25	358	590	616.9	305
104102546270149	25.4	370	609	636.8	314
104102606270149	26	388	638.1	667.3	329
104102706270149	27	418	688.1	719.6	355
104102806270149	28	449	740.1	773.9	382
104102866270149	28.6	469	772.1	807.4	399
104102906270149	29	482	793.9	830.1	409.9
104103006270149	30	516	849.6	888.4	439
104103106270149	31	551	907.1	948.6	468
104103206270149	32	587	966.6	1011	499
104103306270149	33	624	1028	1075	531
104103406270149	34	663	1091	1141	563
104103506270149	35	702	1156	1209	597
104103606270149	36	743	1223	1279	632
104103806270149	38	828	1363	1425	704
104104006270149	40	917	1510	1579	780

104104206270149	42	1,011	1665	1741	860
104104306270149	43	1,060	1745	1825	901
104104406270149	44	1,110	1827	1911	944
104104506270149	45	1,161	1911	1999	987
104104606270149	46	1,213	1997	2089	1,031
104104806270149	48	1,321	2175	2274	1,123
104105006270149	50	1,433	2360	2468	1,218
104105206270149	52	1,550	2552	2669	1,318
104105406270149	54	1,671	2753	2878	1,421

Technical data