



Welded Master Link Assembly X-006W

Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.
At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-4

Safety factor: 4:1.

Grade: 10

Part Code	Code	WLL ton	Proof Load kN	For chain gr 10 Ø 3-4 leg mm	Used to single hook acc. to DIN 15401 No.	D mm	A mm	B mm	d mm	a mm	b mm	Weight kg
402100420430	CD-19 + 2 DD+13	4.2	103	6	6	19	160	95	13	54	25	1.5
402100820430	CD-22 + 2 DD+16	8.2	201	7,8	10	22	170	105	16	70	34	2.3
402101070430	CD-28 + 2 DD+19	10.7	262	10	10	28	190	110	19	85	40	4.1
402101570430	CD-32 + 2 DD+22	15.7	385	13	12	32	230	130	22	115	50	6.6
402102220430	CD-36 + 2 DD+28	22.2	544	16	20	36	275	150	28	140	65	10.9

Blueprint

