



Eyebolts - Collared BS 4278:1984

Product information



Sizes marked * are additional and proportional to the specification.
Also available with UNC, UNF, BSF threads.

Warning: Safe working loads quoted refer to the load being applied vertically. Eyebolts need to be down rated when side loading occurs.

Safety factor: 4:1

Part Code	WLL ton	Stock Code bsw	Stock Code unc	A mm	B mm	D mm	E mm	F mm	G mm	H mm	Weight kg
421100010062	0.1	-	-	1/4	22	7	15	9	20	18	0.06
421100250060	0.25	05B0300	05B0360	3/8	22	7	15	9	20	18	0.06
421100050060	0.5	05B0310	05B0370	1/2	29	10	20	12	26	23	0.15
421100090060	0.9	05B0320	05B0380	5/8	36	12	24	14	32	28	0.27
421100140060	1.4	05B0330	05B0390	3/4	45	14	30	17	40	35	0.54
421100200060	2	05B0340	05B0400	7/8	52	17	35	21	46	40	0.85
421100350060	3.5	-	05B0420	1.1/8	65	22	44	26	58	51	1.62
421100450060	4.5	-	05B0430	1.1/4	72	24	48	29	64	56	2.37
421100650060	6.5	-	05B0440	1.1/2	86	29	57	33	76	67	3.81
421100900060	9	-	-	1.3/4	101	34	68	40	90	79	6.27
421101200060	12	-	-	2	115	38	76	46	102	89	9.58