



## Eyebolts - Collared BS 4278:1984 (Metric Thread)

### Product information



Sizes marked \* are additional and proportional to the specification.

Also available with UNC, UNF, BSF threads.

The zinc plated on request.

**Finish:** Self Colour

**Warning:** Safe working loads quoted refer to the load being applied vertically. Eyebolts need to be down rated when side loading occurs.

Part Code	WLL ton	Thread mm	a mm	b mm	c mm	e mm	f mm	g mm	h mm	Weight kg	Delivery time
421100040050	0.4	12	12	22	33	15	7	36	18	0.06	2
421100050050	0.5	14*	14	29	44	20	10	48	23	0.15	-
421100080050	0.8	16	16	29	44	20	10	48	23	0.15	2
421100100050	1	18*	18	36	52	24	12	58	28	0.27	2
421100160050	1.6	20	20	40	59	27	14	65	32	0.38	2
421100160055	1.6	22*	22	45	64	30	14	73	35	0.54	2
421100250055	2.5	24	24	52	77	35	17	84	40	0.85	2
421100250050	2.5	27*	27	58	85	39	20	94	46	1.13	2
421100400050	4	30	30	65	96	44	22	106	51	1.62	2
421100400055	4	33*	33	72	106	48	24	117	56	2.37	-
421100630050	6.3	36	36	81	118	54	27	131	63	3.12	-
421100630055	6.3	39*	39	86	123	57	29	137	67	3.12	-
421100800050	8	42	42	101	148	68	34	164	79	6.45	-
421100800055	8	45*	45	101	148	68	34	164	79	6.45	-
421101000050	10	48	48	101	148	68	34	164	79	6.51	-
421101250050	12.5	52	52	115	168	76	38	186	89	9.58	-
421101600050	16	56	56	128	188	86	43	208	100	12.99	-
421102000050	20	64	64	144	212	96	48	234	112	18.2	-

# Blueprint

