


Elevator



Trulift 6F

Product information



Also available in Warrington construction (6&6/6/1)
Excellent stretch characteristics

Features: High quality six strand lift rope

Material: High Carbon Steel

Marking: According to standard, On Termination ID and CE mark

Finish: Ungalvanised

Standard: EN 12385-5

Fill factor: 0.49

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
106100604130069	6	1,370/1,770	Bright	sZ	17.8	13.8	SupplierStandard	13
106100654130069	6.5	1,370/1,770	Bright	sZ	20.9	16.2	SupplierStandard	15
106100704130069	7	1,370/1,770	Bright	sZ	24.3	18.8	SupplierStandard	18
106100804130069	8	1,370/1,770	Bright	sZ	31.7	24.6	SupplierStandard	23
106100904130069	9	1,370/1,770	Bright	sZ	40.1	31.1	SupplierStandard	29
106101004130069	10	1,370/1,770	Bright	sZ	49.5	38.4	SupplierStandard	36
106101104130069	11	1,370/1,770	Bright	sZ	59.9	46.5	SupplierStandard	43
106101204130069	12	1,370/1,770	Bright	sZ	71.3	55.3	SupplierStandard	52
106101304130069	13	1,370/1,770	Bright	sZ	83.7	64.9	SupplierStandard	61
106101404130069	14	1,370/1,770	Bright	sZ	97	75.3	SupplierStandard	70
106101504130069	15	1,370/1,770	Bright	sZ	111	86.4	SupplierStandard	81
106101604130069	16	1,370/1,770	Bright	sZ	127	98.3	SupplierStandard	92
106101904130069	19	1,370/1,770	Bright	sZ	179	139	SupplierStandard	130
106102204130069	22	1,370/1,770	Bright	sZ	240	186	SupplierStandard	174