

Trulift 6F

Product information



Also available in Warrington construction (6&6/6/1)
Excellent stretch characteristics

Features: High quality six strand lift rope

Material: High Carbon Steel


Marking: According to standard, On Termination ID and CE mark

Finish: Ungalvanised

Standard: EN 12385-5

Fill factor: 0.49

Elevator



| Part Code | Rope Diameter, mm | Steel area mm² | Min. Breaking force kN. 1370/1770 N/mm² | Weight kg/100m |
|------------------|------------------------------|--------------------------------------|---|---------------------------|
| 106100604130069 | 6 | 13.8 | 17.8 | 13 |
| 106100654130069 | 6.5 | 16.2 | 20.9 | 15 |
| 106100704130069 | 7 | 18.8 | 24.3 | 18 |
| 106100804130069 | 8 | 24.6 | 31.7 | 23 |
| 106100904130069 | 9 | 31.1 | 40.1 | 29 |
| 106101004130069 | 10 | 38.4 | 49.5 | 36 |
| 106101104130069 | 11 | 46.5 | 59.9 | 43 |
| 106101204130069 | 12 | 55.3 | 71.3 | 52 |
| 106101304130069 | 13 | 64.9 | 83.7 | 61 |
| 106101404130069 | 14 | 75.3 | 97 | 70 |
| 106101504130069 | 15 | 86.4 | 111 | 81 |
| 106101604130069 | 16 | 98.3 | 127 | 92 |
| 106101904130069 | 19 | 139 | 179 | 130 |
| 106102204130069 | 22 | 186 | 240 | 174 |