


Elevator



Trulift 8S

Product information



Higher strength
Lower stretch
Uniform diameter
Good diameter retention
Improved fatigue performance

Tolerance more than 10 mm: 0% - +5%

Tolerance less than 10 mm: 0% - +6%

Features: High quality steel core lift rope

Material: High Carbon Steel

Marking: According to standard, On Termination ID and CE mark

Finish: Ungalvanised

Standard: EN 12385-5

Fill factor: 0.59

| Part Code | Rope Diameter, mm | Tensile strength N/mm ² | Finish | Rope lay. | Min. Breaking force kN | Steel area mm ² | Lubrication | Weight kg/100m |
|-----------------|----------------------|---------------------------------------|--------|-----------|---------------------------|-------------------------------|------------------|-------------------|
| 106100904020089 | 9 | 1,570 | Bright | sZ | 48 | 38.1 | SupplierStandard | 34 |
| 106101004020089 | 10 | 1,570 | Bright | sZ | 58.5 | 46.6 | SupplierStandard | 41 |
| 106101104020089 | 11 | 1,570 | Bright | sZ | 69.7 | 55.6 | SupplierStandard | 49 |
| 106101204020089 | 12 | 1,570 | Bright | sZ | 83.6 | 66.4 | SupplierStandard | 59 |
| 106101304020089 | 13 | 1,570 | Bright | sZ | 100 | 79.5 | SupplierStandard | 70 |
| 106101404020089 | 14 | 1,570 | Bright | sZ | 116 | 91.8 | SupplierStandard | 81 |
| 106101504020089 | 15 | 1,570 | Bright | sZ | 131 | 104 | SupplierStandard | 92 |
| 106101604020089 | 16 | 1,570 | Bright | sZ | 148 | 118 | SupplierStandard | 105 |