


Ropetex 55

Product information



ROPETEX



Excellent Resistance to Rotation giving over three times more lifting height than a conventional 18 x 7 class rope. Flexibility is optimised by the unique strand and rope construction. Langs Lay construction combines excellent wear characteristics with efficient spooling on the drum.

RopeTex Ropes are lubricated with the very latest High Performance Wire rope lubricants to give excellent corrosion protection, fatigue life combined with low fling off

ISO 4309 Rope Category No: All Diameters **RCN.23-1**

Features: Very High Breaking Load

Material: High Carbon Steel

Marking: According to standard

Finish: Galvanised as standard

Standard: EN 12385-4

Fill factor: 0,64

RCN: 23-1

Part Code	Rope Diameter,	Tensile strength N/mm ²	Finish	Rope lay.	Breaking Load ton	Weight kg/100m	Delivery time
102100806270069	8	1,960	Galvanized	zZ	5.15	27.6	3
102100906270069	9	1,960	Galvanized	zZ	6.52	34.4	3
102101006270069	10	1,960	Galvanized	zZ	8.05	43	-
102101106270069	11	1,960	Galvanized	zZ	9.75	52	3
102101206270069	12	1,960	Galvanized	zZ	11.62	62	-
102101306270069	13	1,960	Galvanized	zZ	13.66	72	3
102101406270069	14	1,960	Galvanized	zZ	15.8	84	3
102101506270069	15	1,960	Galvanized	zZ	18.14	96	3
102101606270069	16	1,960	Galvanized	zZ	20.6	110	3
102101706270069	17	1,960	Galvanized	zZ	23.2	120	-
102101806270069	18	1,960	Galvanized	zZ	26.1	135	3
102101906270069	19	1,960	Galvanized	zZ	29.1	150	3
102102006270069	20	1,960	Galvanized	zZ	32.2	166	3
102102206270069	22	1,960	Galvanized	zZ	38.94	201	3
102102406270069	24	1,960	Galvanized	zZ	46.38	245	3
102102606270069	26	1,960	Galvanized	zZ	53.72	297	-
102102806270069	28	1,960	Galvanized	zZ	62.38	345	-