



Ordinary Thimble BS 464:1958

Product information

Manufactured in the UK

Standard: BS 464-1 :1958

Features: Thimbles to give protection to the eye of the wire rope

Material: Steel

Marking: Manufacturer's symbol

Finish: Galvanised

| Part Code | Rope Ø range mm | Rope diameter inch | a mm | b mm | c mm | d mm | e mm | Weight kg/100pc | Delivery time |
|--------------|--------------------|-----------------------|---------|---------|---------|---------|---------|--------------------|---------------|
| 123100630110 | 6.3 | 1/4 | 6 | 48 | 30 | 20 | 3.5 | 3.5 | 3 |
| 123100790110 | 7.9 | 5/16 | 8 | 54 | 33 | 22 | 4 | 4.5 | 3 |
| 123100950110 | 9.5 | 3/8 | 10 | 64 | 38 | 25 | 4.8 | 8.5 | 3 |
| 123101270110 | 12.7 | 1/2 | 14 | 80 | 44 | 32 | 5.6 | 14 | 3 |
| 123101430110 | 14.3 | 9/16 | 15 | 80 | 44 | 32 | 5.6 | 14 | - |
| 123101590110 | 15.9 | 5/8 | 17 | 98 | 59 | 41 | 7.9 | 22.5 | 3 |
| 123101750110 | 17.5 | 11/16 | 19 | 108 | 67 | 44 | 7.9 | 45 | 3 |
| 123101910110 | 19.1 | 3/4 | 20 | 124 | 73 | 51 | 9.5 | 45 | 3 |
| 123102220110 | 22.2 | 7/8 | 23 | 133 | 83 | 57 | 9.5 | 55 | 3 |
| 123102380110 | 23.8 | 15/16 | 25 | 146 | 92 | 64 | 10.3 | 76 | 3 |
| 123102540110 | 25.4 | 1 | 27 | 162 | 108 | 70 | 10.3 | 98 | 3 |
| 123102860110 | 28.6 | 1.1/8 | 29 | 178 | 111 | 76 | 12.7 | 141 | 3 |
| 123103180110 | 31.8 | 1.1/4 | 33 | 197 | 133 | 95 | 12.7 | 164 | 3 |
| 123103490110 | 34.9 | 1.3/8 | 38 | 229 | 152 | 105 | 15.9 | 221 | 3 |
| 123103810110 | 38.1 | 1.1/2 | 41 | 254 | 165 | 114 | 17.5 | 371 | 3 |
| 123104130110 | 41.3 | 1.5/8 | 46 | 254 | 165 | 114 | 17.5 | 499 | - |
| 123104450110 | 44.5 | 1.3/4 | 51 | 286 | 178 | 127 | 25.4 | 582 | 3 |
| 123104760110 | 47.6 | 1.7/8 | 60 | 318 | 191 | 133 | 28.6 | 740 | - |
| 123105080110 | 50.8 | 2 | 64 | 330 | 203 | 140 | 28.6 | 799 | - |

Blueprint

