

## Cablegrip Open

### Product information



**General:** Open Ended Cablegrip ideal for joining two cables to form a continuous loop. Typical application: replacement of elevator cables, where the old cable would be attached to the new one, and the cable then fed round with ease.

**Design:** Pleated of double wire ropes.

**Material:** Steel wire rope - Galvanized.

**Note:** Substantial safety ratios have been applied to all quoted minimum-breaking strengths. Additional safety factors, determined by application, should be applied. CERTEX recommends a minimum saf

Part Code	Code	Rope Ø range mm	MBL	L mm	Supplier code cable grips (minehead)	Weight kg	Delivery time
140601600020	KO-0	8-16	1,504	1,200	612/8	0.25	-
140602000020	KO-1	10-20	1,860	1,200	612/10	0.3	3
140603000020	KO-2	20-30	2,256	1,200	612/20	0.35	3
140604000020	KO-3	30-40	3,696	1,200	612/30	0.64	3
140605000020	KO-4	40-50	5,490	1,200	612/40	1	3
140606500020	KO-5	50-65	5,490	1,200	612/50	1.1	3
140608000020	KO-15	65-80	7,320	1,800	618/65	2.2	-
140609500020	KO-16	80-95	9,150	1,800	618/80	2.3	-
140611000020	KO-17	95-110	12,736	1,800	618/95	4.4	-