



Lever Hoist Bulldog 750KG-6t

Product information

- Super strength alloy loadchain
- Minimum effort to raise maximum load
- Fully enclosed gear train
- Weather protected automatic Weston brake
- Fully machined liftwheel
- Cast steel safety latches
- Malleable hook forgings
- All gears and shafts running on roller bearings
- Durable baked enamel paint protection
- Spare parts always available
- Overload protection as standard

Standard: EN 13157: 2004

Loadsafe Overload Protection

Certex have introduced overload protection for their quality range of lever hoists and chain blocks. When lifting with conventional blocks there is no safeguard incorporated in the design of the chain block for the prevention of overload damage.

Unfortunately it is all too common practise to extend the leverage by adding either a longer pipe to the lever hoist handle or using additional personnel to increase the manual effort on the hand chain when the lifting effort becomes too great.

The Bulldog range has a simple solution that prevents a load being lifted if it is excess of a preset level. Using a special clutch mechanism, this prevents the equipment from being damaged by overloading.

Certex are the pioneers in offering this feature as standard for their range of chain blocks and lever hoists. As the additional cost to the operator will be minimal this offers a full proof safety system in the prevention of damage to the equipment by overloading, thus avoiding expensive repair costs

Features: Robust all-steel construction

Marking: WLL, code and CE marking.

Finish: Durable baked enamel paint protection

Safety factor: 4:1

Part Code	WLL ton	Lifting height m	Number of falls	A mm	B mm	C mm	D mm	E mm	H mm	Weight kg	Delivery time
501100080150070	0.75	1.5	1	148	90	136	280	30	325	7	-
501100150150070	1.5	1.5	1	172	98	160	410	35	380	11	-
501100300150070	3	1.5	1	200	115	180	410	40	480	21	-
501100600150070	6	1.5	2	200	115	235	410	50	620	31	2

Blueprint

