

## Horizontal Lifting Clamp IPHOZ



### Product information

**General:**

The IPHOZ horizontal lifting clamp is to be used for lifting and transferring, in the horizontal position, of thin sheet and other materials that will sag or bend when lifted. These clamps must be used in pairs or more.

**Features:**

- Available in capacities of .75 thru 15 metric tons.
- Wide variety of jaw openings available: 0 to 60mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked

**Standard:** EN 13155

**Warning:** Only to be used in pairs.

Part Code	WLL ton	Jaw width mm	I P Model.	B mm	C mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	Weight kg
502100080300300	0.75	0-30	0.75-IPHOZ	94	16	16	70	118	81	12	31	12	3
502100150450300	1.5	0-45	1.5-IPHOZ	133	16	22	125	192	100	16	36	12	5.5
502100300450300	3	0-45	3-IPHOZ	137	20	26	125	200	120	20	48	10	8
502100450450300	4.5	0-45	4.5-IPHOZ	138	25	30	126	220	120	20	50	10	8.5
502100600600300	6	0-60	6-IPHOZ	171	30	36	135	235	130	20	56	20	15.5
502100900600300	9	0-60	9-IPHOZ	211	30	43	166	276	160	25	62	20	20.5
502101200600300	12	0-60	12-IPHOZ	217	40	47	168	294	190	25	62	-	38
502101500600300	15	0-60	15-IPHOZ	220	40	47	183	317	250	25	62	22	38

## Blueprint

