

## Screw Pin Chain Shackle Crosby G-210

### Product information

**Design:** Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

**Material:** Forged - Quenched and Tempered, with alloy pins.

**Marking:** According to standard, CE-marked

**Temperature range:** -40° C to 204° C

**Finish:** Hot Dip galvanized or self colored.

**Standard:** EN 13889, US. FED. SPEC. RR-C-271F

**Safety factor:** 6:1

**Grade:** 6



Part Code	WLL ton	Size inch	Weight kg	Delivery time
420100050030	0.5	1/4	0.05	2
420100750030	0.75	5/16	0.08	2
420100100030	1	3/8	0.13	-
420100150030	1.5	7/16	0.2	2
420100200030	2	1/2	0.27	-
420100330030	3.25	5/8	0.57	2
420100480030	4.75	3/4	1.19	2
420100650030	6.5	7/8	1.43	2
420100850030	8.5	1	2.15	-
420100950030	9.5	11/8	3.06	2
420101200030	12	11/4	4.11	2
420101350030	13.5	13/8	5.28	-
420101700030	17	11/2	7.23	2
420102500030	25	13/4	12.13	-
420103500030	35	2	19.19	-
420105500030	55	21/2	32.55	-

# Blueprint

