

## Screw Pin Anchor Shackle Crosby G-209



### Product information

Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

**Proof load:** 2 x WLL.

**Material:** Carbon steel with headbolt in alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +204°C

**Finish:** Hot dip galvanized.

**Standard:** EN 13889

**Safety factor:** 6:1

**Grade:** 6

Part Code	WLL ton	Size inch	Weight kg	Delivery time
420100030190	0.33	3/16	0.03	2
420100050190	0.5	1/4	0.05	2
420100750190	0.75	5/16	0.09	2
420100100190	1	3/8	0.14	2
420100150190	1.5	7/16	0.17	2
420100200190	2	1/2	0.33	2
420100330190	3.25	5/8	0.62	2
420100480190	4.75	3/4	1.07	2
420100650190	6.5	7/8	1.64	2
420100850190	8.5	1	2.28	2
420100950190	9.5	1 1/8	3.36	2
420101200190	12	1 1/4	4.31	2
420101350190	13.5	1 3/8	6.14	2
420101700190	17	1 1/2	7.8	2
420102500190	25	1 3/4	12.6	-
420103500190	35	2	20.4	2
420105500190	55	2 1/2	38.9	2

# Blueprint

