

Screw Pin Anchor Shackle Crosby G-209



Product information

Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

Proof load: 2 x WLL.

Material: Carbon steel with headbolt in alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to +204°C

Finish: Hot dip galvanized.

Standard: EN 13889

Safety factor: 6:1

Grade: 6

Part Code	WLL ton	Nominal size In.	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L mm	M mm	P mm	Weight kg	Delivery time
420100030190	0.33	3/16	9,65	6,35	22,4	4,85	15,2	14,2	24,9	37,3	4,06	28,4	4,85	0.03	2
420100050190	0.5	1/4	11,9	7,85	28,7	6,35	19,8	15,5	32,5	46,7	4,85	35,1	6,35	0.05	2
420100750190	0.75	5/16	13,5	9,65	31,0	7,85	21,3	19,1	37,3	53,0	5,60	42,2	7,85	0.09	2
420100100190	1	3/8	16,8	11,2	36,6	9,65	26,2	23,1	45,2	63,0	6,35	51,5	9,65	0.14	2
420100150190	1.5	7/16	19,1	12,7	42,9	11,2	29,5	26,9	51,5	74,0	7,85	60,5	11,2	0.17	2
420100200190	2	1/2	20,6	16,0	47,8	12,7	33,3	30,2	58,5	83,5	9,65	68,5	12,7	0.33	2
420100330190	3.25	5/8	26,9	19,1	60,5	16,0	42,9	38,1	74,5	106	11,2	85,0	17,5	0.62	2
420100480190	4.75	3/4	31,8	22,4	71,5	19,1	51,0	46,0	89,0	126	12,7	101	20,6	1.07	2
420100650190	6.5	7/8	36,6	25,4	84,0	22,4	58,0	53,0	102	148	12,7	114	24,6	1.64	2
420100850190	8.5	1	42,9	28,7	95,5	25,4	68,5	60,5	119	167	14,2	129	26,9	2.28	-
420100950190	9.5	1 1/8	46,0	31,8	108	29,5	74,0	68,5	131	190	16,0	142	31,8	3.36	2
420101200190	12	1 1/4	51,5	35,1	119	32,8	82,5	76,0	146	210	17,5	156	35,1	4.31	2
420101350190	13.5	1 3/8	57,0	38,1	133	36,1	92,0	84,0	162	233	19,1	174	38,1	6.14	2
420101700190	17	1 1/2	60,5	41,4	146	39,1	98,5	92,0	175	254	20,6	187	41,1	7.8	2
420102500190	25	1 3/4	73,0	51,0	178	46,7	127	106	225	313	25,4	231	57,0	12.6	-
420103500190	35	2	82,5	57,0	197	53,0	146	122	253	348	31,0	263	61,0	20.4	2
420105500190	55	2 1/2	105	70,0	267	69,0	184	145	327	453	35,1	330	79,5	38.9	2

Blueprint

