

## Bolt Type Chain Shackle Crosby G-2150



### Product information

**Design:** Bolt Type Chain shackle. Thin hex head bolt/nut with cotter pin.

Meets the performance requirements of Federal Specification RR-C-271H, Type IVB, Grade A, Class 3, except for those provisions required of the contractor.

**Material:** Forged — Quenched and Tempered, with alloy pins.

**Marking:** According to standard, CE-marked

**Finish:** Hot Dip galvanized or self colored.

**Standard:** EN 13889

**Safety factor:** 6:1

**Grade:** 6

Part Code	WLL ton	Nominal Size (in.)	A mm	B mm	D mm	F mm	G mm	K mm	M mm	P mm	R mm	A Tolerance +/-	G Tolerance +/-	Weight kg	Delivery time
420100050040	0.5	1/4	11.9	7.9	6.4	15.5	19.1	40.4	24.6	39.6	6.35	1.5	1.5	0.06	-
420100750040	0.75	5/16	13.5	9.7	7.9	19.1	25.4	48.5	29.5	46.2	7.85	1.5	1.5	0.1	2
420100100040	1	3/8	16.8	11.2	9.7	23.1	31	58.5	35.8	55	9.65	1.5	3.3	0.15	-
420100150040	1.5	7/16	19.1	12.7	11.2	26.9	36.1	67.5	41.4	63.5	11.2	1.5	3.3	0.22	-
420100200040	2	1/2	20.6	16	12.7	30.2	41.4	77	46	71	12.7	1.5	3.3	0.34	2
420100330040	3.25	5/8	26.9	19.1	16	38.1	51	95.5	58.5	89.5	16	1.5	3.3	0.67	-
420100480040	4.75	3/4	31.8	22.4	19.1	46	60.5	115	70	103	20.6	1.5	6.35	1.14	-
420100650040	6.5	7/8	36.6	25.4	22.4	53	71.5	135	81	120	24.6	1.5	6.35	1.74	2
420100850040	8.5	1	42.9	28.7	25.4	60.5	81	151	93.5	135	25.4	1.5	6.35	2.52	2
420100950040	9.5	1-1/8	46	31.8	28.7	68.5	91	172	103	150	31.8	1.5	6.35	3.45	2
420101200040	12	1-1/4	51.5	35.1	31.8	76	100	191	115	165	35.1	1.5	6.35	4.9	2
420101350040	13.5	1-3/8	57	38.1	35.1	84	111	210	127	183	38.1	3.3	6.35	6.24	-
420101700040	17	1-1/2	60.5	41.4	38.1	92	122	230	137	196	41.1	3.3	6.35	7.72	-
420102500040	25	1-3/4	73	51	44.5	106	146	279	162	230	54	3.3	6.35	14.2	-
420103500040	35	2	82.5	57	51	122	172	312	184	264	60	3.3	6.35	21.2	-
420105500040	55	2-1/2	105	70	66.5	145	203	377	238	344	66.5	6.35	6.35	38.6	-
420108500040	85	3 †	127	82.5	76	165	216	429	279	419	89	6.35	6.35	56	-

# Blueprint

