

## Thimble G-414, Crosby - Extra heavy

### Product information

**General:**

The use of the G-414 extra heavy thimbles for your wire rope slings ensures a greater protection against wear of the wire rope and deformation of the wire rope eye.

**Features:**

- Longer service life.

**Material:** Steel

**Marking:** According to standard

**Finish:** Hot-dip galvanised

**Standard:** EN 13411-1



Part Code	Rope Ø range mm	Finish	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg/100pc	Delivery time
123100700230	6-7	Galvanized	55.5	41.4	38.1	22.4	11,2	7.1	1.5	5.85	3	-
123100800230	8	Galvanized	63.5	47.8	46	26.9	14,0	8.65	2.05	7.1	5.35	-
123101000230	9-10	Galvanized	73,0	54,0	54	28.7	16,8	10.4	2.8	8.65	9.8	-
123101200230	11-12	Galvanized	82.5	60.5	60.5	31.8	18.8	11.9	3.3	9.65	15.7	-
123101500230	13-15	Galvanized	92,0	70,0	70,0	38.1	23.4	13,5	3.55	10.4	23.1	3
123101600230	16	Galvanized	108	82.5	79.5	44.5	26,2	16.8	4.05	12.7	34.3	-
123102000230	18-20	Galvanized	127	95.5	96,5	51	33,0	19.8	5.6	16.8	72	-
123102200230	22	Galvanized	140	108	108	57	37,3	23.9	5.6	19.1	81	3
123102600230	24-26	Galvanized	156	114	125	63.5	44,5	26.9	6.35	22.4	142	-
123103200230	28-32	Galvanized	178	130	149	73	47,8	33.3	6.35	28.7	181	-
123103500230	32-35	Galvanized	230	165	173	89	57,2	36.6	9.65	28.7	402	-
123103800230	35-38	Galvanized	229	159	181	89	66,5	39.6	12.7	28.7	587	-
123104000230	40	Galvanized	286	203	207	102	76,2	43.7	12.7	35.1	771	-
123104400230	44	Galvanized	310	229	216	114	77,7	46.7	12.7	33.3	805	-
123105200230	48-52	Galvanized	384	305	264	152	85,9	53,0	12.7	38.1	1,259	-
123105600230	56	Galvanized	435	356	302	178	98,6	60.5	16,0	41.4	1,792	-

# Blueprint

