

Protection EXTREEMA®

Product information

LIFT-TEX®

HEAVY LIFT SLINGS

EXTREEMA® Protections

Round slings should be protected from sharp edges, abrasion and tear, both on the side of the load as well as on the lifting device. In case a protection against damage of the sides or against tear is supplied as a part of the round sling, the protections should be applied as described. An additional protection can be mandatory.

Standard: EN 1492.

Why EXTREEMA® Protection?

Very good features:

- High cut resistance.
- High tear resistance (with HMPE Dyneema® Sleeves).
- High abrasion resistance.
- Good resistance to chemicals.
- Good resistance to sea water.
- Does not take up water.
- In many configurations.

EXTREEMA® Protections with Dyneema®

EXTREEMA® L-series - with velcro.

EXTREEMA® XL-series - protective sleeve.

EXTREEMA® XXL-series - protective.

Standard: EN 1492-1 & EN 1492-2.

Temperature range: -50°C up to +70°C



Code	Width mm	Length cm
EP-L0	80	100
EP-L10	500	100
EP-L1	120	100
EP-L11	550	100
EP-L12	600	100
EP-L13	700	100
EP-L14	800	100
EP-L15	900	100
EP-L16	1,000	100
EP-L2	150	100
EP-L3	180	100
EP-L4	200	100
EP-L5	250	100
EP-L6	300	100
EP-L7	350	100
EP-L8	400	100
EP-L9	450	100

Technical data

Size chart

Code	Polyester round sling		Extreema round sling		PES webbing sling
	Single leg	Double leg	Single leg	Double leg	
	ton		ton		width (mm)
EP-L1	1-4	N/A	1-5	N/A	30
EP-L2	5	1-2	6-10	1-5	50
EP-L3	N/A	3-4	12	6-10	N/A
EP-L4	5	5	N/A	12-15	75
EP-L5	12	6-10	20-45	N/A	90
EP-L6	20	12	50-70	20-45	120
EP-L7	25-30	15	80-90	50/70	150
EP-L8	N/A	20	100	80-90	180
EP-L9	N/A	25	N/A	100	N/A
EP-L10	N/A	30	N/A	N/A	N/A
EP-L11	N/A	N/A	N/A	N/A	240
EP-L12	N/A	N/A	N/A	N/A	N/A
EP-L13	N/A	N/A	N/A	N/A	300