


## Open Spelter socket OSS



### Product information



**General:** Forged clevis fittings for embedment with cast compound. Delivered complete with bolt and cotter pin.

**WARNING!:** Compare the spelter's and the wire rope's minimum breaking load.

**Finish:** Galvanized.

**Note:** For intermediate rope diameter select fittings with nearest following size.

Code	Rope Ø range mm	MBL	Finish	N mm	A mm	C mm	D mm	F mm	J mm	L mm	M mm	Weight kg
OSS-196 P	6-7	8	Galvanized	9	109	19	16	8,5	50	40	34	0.4
OSS-197 P	8-10	12	Galvanized	11	124	21	20,6	12	57	45	42	0.8
OSS-198 P	11-13	20	Galvanized	12	142	25	25	14	64	51	50	1
OSS-199 P	14-16	25	Galvanized	14	171	32	30	17,5	76	63	58	1.8
OSS-100 P	18-19	40	Galvanized	16	205	38	35	21	89	76	70	3.2
OSS-104 P	20-22	55	Galvanized	19	235	44	41	24	101	89	80	4.6
OSS-108 P	23-26	75	Galvanized	22	275	51	51	28	114	101	104	8
OSS-111 P	27-30	90	Galvanized	25	306	57	57	32	127	114	114	11
OSS-115 P	31-36	125	Galvanized	28	338	63	63	38	139	127	126	16
OSS-118 P	37-39	150	Galvanized	30	394	76	70	41	152	162	142	23
OSS-120 P	40-42	170	Galvanized	33	418	76	76	44	165	165	152	27
OSS-125 P	43-48	225	Galvanized	39	468	89	89	51	190	178	176	41
OSS-128 P	49-54	280	Galvanized	46	552	101	95	57	216	228	194	58
OSS-130 P	55-60	360	Galvanized	53	598	113	108	63	228	250	210	85

# Blueprint

